

# Tough and resilient DMR Tier 2 conventional node for mission-critical networks.

The Tait TN9300-2 is at the heart of Tait Digital Mobile Radio (DMR) Tier 2 conventional single or multiple site networks.

This reliable node consolidates the control, monitoring and programming of Tier 2 networks as well as providing multiple interfaces for external applications.



## KEY FEATURES

- Tough design and build with no moving parts, and sealed to limit dust ingress and protection in salt fog environments
- Resilient and reliable with a 100% processing load in a 65°C ambient environment
- Low power consumption
- Software support for single or multisite services
- Multiple interfaces – AIS, SIP, RIP, API

### FEATURES AND BENEFITS

#### Tough, Rugged Enclosure

- Solid machined block
- Fan less cooling
- Solid construction

#### Reliability and Resilience

- No moving parts
- Solid state drive
- 100% processing even at 65°C ambient temperatures

#### Environmental protection

- Sealed from dust
- Protected from salt fog atmospheres
- Suitable for hostile environments
- Wide power range

#### Low power consumption

- Energy efficient design
- Idle power demand 11W
- Battery backed solution option

#### Interfaces

- Ethernet
- USB (3)
- HDMI for future display options

#### Single site / single repeater control

- Provides AIS interface to console
- Recorder interface
- Restful applications interface
- Console pre-emption
- Emergency support


#### Multisite / multi repeater control

- Provides AIS interface to console(s)
- Recorder interface(s)
- Applications interface(s)
- Consolidation of monitoring and reprogramming
- Console pre-emption
- Emergency support

#### Partner support

- Omnitronics Console over AIS
- AVL on Omnitronics over monitoring API
- Eventide voice recorder
- NextLog

\* Not all features are supported in all modes of operation. Feature comparison tables are available in the full product catalog.



Note: The TN9300-2 node is not required if RF dispatch radio operation is the only control required with a TB9300 DMR Tier 2 base station.

# TN9300-2

## SPECIFICATIONS

### GENERAL TN9300-2 HARDWARE SPECIFICATIONS

Supported servers Aleutia R50, Dell R230, Kontron CG2300

### CONNECTIVITY DETAILS

|   |  |
|---|--|
| WAN speed to requirement per slot, voice and data | 32Kbps   |
| WAN jitter  | Less than 20mS   |
| WAN Latency (maximum acceptable)                  | 100mS  |
| WAN bandwidth for reprogramming, monitoring, etc  | 100Kbps  |
| Multisite Capacity                                | 20 Sites extensively tested (require capacity for more contact Tait) |
| Maximum channel capacity                          | Up to 40 RF physical channels (80 logical)                           |

### INTERFACE CAPABILITY

|                               |                     |
|-------------------------------|---------------------|
| Console connectivity          | AIS(DMRA standard)  |
| Recorder interface            | VR (Voice Recorder) |
| Location services application | Tait Monitoring API |

Tait has taken every care in compiling this specification sheet, but we're always innovating and therefore changes to our models, designs, technical specification, visuals and other information included in this specification sheet could occur. For the most up-to-date information and for a copy of our terms and conditions please visit our website [www.taitradio.com](http://www.taitradio.com).

\* Tait cannot guarantee full performance to the published specifications when the radio is operating at frequencies outside the specified range.

For further information please check with your nearest Tait office or authorized dealer.

Tait International Limited facilities are certified for ISO 9001:2015 (Quality Management System), ISO 14001:2015 (Environmental Management System) and BS OHSAS 18001:2007 (Occupational Health and Safety Management System) for aspects associated with the design, manufacture and distribution of radio communications and control equipment, systems and services. In addition, all our Regional Head Offices are certified to ISO 9001.

The word "Tait" and the Tait logo are trademarks of Tait International Limited.

#### Authorized Partners

